FURUNO


FISH SPECIES AND BIOMASS SOUNDER







High-end Fish Finder with newly



FISH SPECIES AND BIOMASS SOUNDER

Model **F55-3BB**

The FURUNO Fish Species and Biomass Sounder model FSS-3BB is equipped with a brand new revolutionary technology, the IDENTI-FISH™ function, which supports the identification of fish species in real time during fishing operation. IDENTI-FISH™ function not only improves the efficiency of fishing operation, but also contributes to sustainable fishery by supporting the prevention of by-catch.

The IDENTI-FISH™ function consists of the IDENTI-FISH™ echo display and the IDENTI-FISH™ histogram. The IDENTI-FISH™ echo is a combination of high and low frequency echoes, while the IDENTI-FISH™ histogram shows the distribution of echo pattern in the selected area. One of the characteristics of IDENTI-FISH™ is the capability to view swim-bladderless fish, such as Atlantic mackerel, much clearer than before, using both the IDENTI-FISH™ echo and the IDENTI-FISH™ histogram. A mixed school of Atlantic mackerel and Herring is identified using IDENTI-FISH™. IDENTI-FISH™ also allows you to register your own histogram curves for different species you have encountered.

The FURUNO FSS-3BB combines the benefits of both the latest fishing innovations and powerful customization capabilities to help ensure the success of your operation.

IDENTI-FISH™ function*1!

- → 3 kW TruEcho CHIRP™ Fish Finder
- Simultaneous transmission
- ► The IDENTI-FISHTM graph^{*1} indicates the degree of similarity of fish species^{*2} by histograms and numerical values.
- ► The IDENTI-FISH™ echo display distinguishes swim-bladderless fish like Atlantic mackerel and fish with a swim bladder like herring.
- ► Fish-size graph*¹ allows estimation of fish size distribution in three locations at a glance.
- ▶ Data recording and screenshot function for easy review of past echoes and recordings
- Scroll back mode allows the user to review past data.
- ▶ Recorded data can be saved to an external data storage device.
- ► Easy access to Gain setting is applied to all screens including high frequency, low frequency and IDENTI-FISH™ echo display.
- ► Net sensor information*3 can be shown on the display.
- ► Constant and stable display of echoes is achievable with the use of the heave offset function*4.
- ▶ Geographical location of schools of fish can be output to connected navigational equipment.
- Dual monitor installation is available.
- Simple operation with the Trackball Control Unit and Instant Access bar™
- ▶ Separate processor unit and transceiver unit allow installation in large size ships.
- *1 Compatible transducer is required.
- *2 The model data saved to the system are Atlantic mackerel and herring. You can register a fish species name in the model data and create own reference curves.
- *3 Compatible models: TE-155 (Marport), TS-337A (Imaginex) and ITI System (Simrad)
- *4 SATELLITE COMPASS™ is required.

left: High/Low frequency echo display right: IDENTI-FISH™ echo display



The IDENTI-FISH™ function* helps you prevent l

NEW


IDENTI-FISH™ function*

New IDENTI-FISH™ function consists of an echo display and a graphic histogram.


IDENTI-FISH™ echo display

The IDENTI-FISH™ echo display is a combined echogram of high and low frequency echo.


This mode allows you to visualize a difference of the echo between swim bladder fish and swim-bladderless fish.



When the color of echo is red-brown on the IDENTI-FISH™ echo display, you will be able to deduce that it is a school of fish with swim bladder like herring. On the other hand, if it is light green colored echo, you can assume it is probably swim-bladderless fish like Atlantic mackerel, as shown in the screenshot below.



Echoes of school of swim bladder fish. (Displayed in red-brown color.)




Echoes of school of swim-bladderless fish. (Displayed in light green color.)


y-catches and contributes to sustainable fishery.

* Compatible transducer is required.

The IDENTI-FISH™ echo function displays echoes with different color depending on the fish species so that you can quickly identify the species and their distribution even when mixed together.





The following picture shows that the FSS-3BB is capable of identifying swim-bladderless fish. In this example, the Atlantic mackerel echo is displayed in light green.



IDENTI-FISH™ histogram graph

The IDENTI-FISH™ graph compares the histograms of the school of fish within the measurement range with the model data, and indicates the similarity of fish species by numerical values and bar graphs. The default model data saved to the system are Atlantic mackerel and herring. You can add new fish species in the model data and create own reference curves for any fish species. Two areas of the echogram can be measured and analyzed simultaneously.






In the upper right example, the yellow line represents a reference curve of Atlantic mackerel. The red line represents a reference curve of herring. The blue line shows actual echo distribution pattern as measured in the selected area on the IDENTI-FISHTM echo display. The blue line is almost identical to the red line which is a reference curve of herring, and the degree of similarity indicates herring with 98% accuracy, you can therefore assume, with a high level of confidence, that it is indeed a school of herring.

The combination of the IDENTI-FISH™ echo display and the histogram graph is useful for distinguishing fish species. The FSS-3BB can be customized as a dedicated fish finder for each user with this unique function.


Accurate fish size measurements in easy-to-understand graph form**

The FSS-3BB measures the size and distribution of fish in the selected school, and displays this information in a graph that can be understood at a glance. TruEcho CHIRPTM technology has improved the accuracy and reliability of fish size measurements and graphs (max.3). This function allows you to compare and analyze the size of fish and the density of schools, which are key data when aiming for fish of a particular size.

** Fish length is a reference value calculated from reflection intensity. Compatible transducer is required.



The FSS-3BB has four methods of fish size measurement. You can select your favorite measurement method from Instant Access bar by just clicking on the menu button.




Echo display with the alternate transmission

Simultaneous transmission

The echo-update rate is doubled by applying simultaneous transmission, which provides more rich presentation of school of fish.


Echo display with the simultaneous transmission



Overlay of depth line by connecting net sensor


Net sensor information can be shown on the display*.


* Compatible models are TE-155 (Marport), TS-337A (Imaginex) and ITI System (Simrad). The initial setting is required.



Screenshots and echo data can be recorded and play back

A maximum of 999 screenshots can be saved on the processor unit. You can also replay the echo display at any time if you wish to see it again. This is helpful in comparing the sizes of schools of fish. For external memory devices*, the number of files that can be saved depends on the capacity of the device.





Easy and quick operation

The screen header also contains Range, Shift, Sensitivity, Image Feed and Display Mode menus. These functions can be accessed immediately and adjusted by just turning the wheel in the control unit.




The FSS-3BB can be operated easily and quickly with its trackball controller.



Other functions can also be accessed immediately from the InstantAccess bar TM . Up to 10 functions can be added to the InstantAccess bar TM





FISH SPECIES AND BIOMASS SOUNDER

Model F55-3BB

GENGERAL

15 to 242 kHz nominal Transmitting frequency

Output power 1 to 3 kW

Transmitting method Dual simultaneously

Transmitting mode CW/FM

External monitor (required specs.)

1920 x 1200 (WUXGA), 1920 x 1080 (FHD), Resolution:

1600 x 1200 (UXGA),

1024 x 1280 (SXGA), 1024 x 768 (XGA)

Interface: HDMI type-A

PROCESSOR UNIT

Color Indication 64/16 colors

7 steps (Standard, Hue 1 to 5, customized) Hue

Depth range 5 to 3000 m 2000 m max. Range shift Expansion range 5 to 200 m

Echo display mode High/Low frequency single, Dual frequency,

Discrimination

Zoom display Bottom-lock expansion, Bottom zoom,

Marker zoom, Discrimination zoom

Fish size histogram Histogram

7 steps (Lines/TX: Freeze, 1/8, 1/4, 1/2, 1/1, Display advance speed

2/1, 4/1)

Danish, English (UK/US), French, Japanese, Language

Norwegian, Spanish

INTERFACE

Number of ports

Serial 5 ports, NMEA0183 Ver.1.5/2.0/3.0 LAN 2 ports, Ethernet, 10/100/1000Base-T USB USB2.0: 2 ports, USB3.0: 2 ports Video output 2 ports, HDMI type-A

KP control (transceiver unit) 1 port

Data Sentences

Input: GGA, GLL, GNS, MTW, VHW, VTG,

ZDA, GPatt, GPhve, pireq, IIDAD, IIDBS, IIHFB, IITPC, IITPT, MPMSD,

SDDBS, SDfnz

Output: DBS, DBT, DPT, MTW, TLL, SDes1, SDes2, SD3sd, SDflg, SDmrk, pidat

POWER SUPPLY

12-24 VDC, 4.0-2.0 A Processor unit

12-24 VDC, 8.3-4.1 A (St-by: 0.79-0.46 A) Transceiver unit Rectifier 100/110/115/220/230 VAC, 1 phase, 50/60 Hz

ENVIRONMENTAL CONDITIONS

Ambient temperature -15°C to +55°C Relative humidity 93% or less at +40°C

Processor/Transceiver unit: IP22 Degree of protection

Control unit: IP22 (IPx0: USB cover opened)

Vibration: IEC60945 Ed.4

EQUIPMENT LIST

Standard

1.Processor unit FSS-301 1 unit 2. Transceiver unit FSS-302 1 unit 3. Trackball control unit RCU-026

Option

1.Transducer

2.Trackball control unit RCU-026

3.Rectifier unit RU-1746B-2

4.DVI/USB repeater TM000-FDX06 (TXRX_30M, 50M, 100M, TXRX, RX, TX)

5.Flush mount OP24-27 (for RCU-026)

6.Cable assembly

7.Extension cable (for transducer)

8.Installation materials

List of CHIRP Transducers for FSS-3BB


Type*	Frequency	Output Power	Cable length	Available funcitons
CM265LHG	42 to 65 kHz/130 to 210 kHz	1 kW/1 kW	12 m	•
CM265LM	42 to 65 kHz/85 to 135 kHz	1 kW/1 kW	12 m	
CM275LHW	42 to 65 kHz/150 to 250 kHz	1 kW/1 kW	12 m	
CM599LHG	28 to 60 kHz/130 to 210 kHz	3 kW/2 kW	15 m	•
CM599LM	28 to 60 kHz/80 to 130 kHz	3 kW/2 kW	15 m	
CM599LHW	28 to 60 kHz/130 to 210 kHz	3 kW/1 kW	15 m	
PM111LHG	38 to 75 kHz/80 to 130 kHz	2 kW/2 kW	15 m	0
PM111LM	38 to 75 kHz/80 to 130 kHz	2 kW/2 kW	15 m	
PM411LWM	40 to 60 kHz/80 to 130 kHz	2 kW/2 kW	15 m	

* Airmar model name ●Fish size histgram and IDENTI-FISH™

OFish size histgram


Processor Unit






Transceiver Unit (Bulkhead/Tabletop mount)

FSS-302 10 kg 22 lb



DVI/USB repeater


TM000-FDX06 TX/RX 1.4 kg 3.1 lb






Trackball Control Unit RCU-026

Flush Mount 1.5 kg 3.3 lb



Fixture Mount 1.5 kg 3.3 lb



4.Installation materials

Beware of similar products

All brand and product names are registered trademarks, trademarks or service marks of their respective holders.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

FURUNO ELECTRIC CO., LTD.

FURUNO U.S.A., INC.

FURUNO PANAMA S.A. **FURUNO (UK) LIMITED**

FURUNO NORGE A/S

FURUNO DANMARK A/S FURUNO SVERIGE AB

FURUNO FINLAND OY

FURUNO POLSKA Sp. Z o.o. **FURUNO DEUTSCHLAND GmbH** **FURUNO ESPAÑA S.A. FURUNO ITALIA S.R.L. FURUNO HELLAS S.A. FURUNO (CYPRUS) LTD**

FURUNO FRANCE S.A.S.

FURUNO EURUS LLC

FURUNO SHANGHAI CO., LTD.

FURUNO CHINA CO., LTD. Hong Kong | www.furu **FURUNO SINGAPORE**

PT FURUNO ELECTRIC INDONESIA FURUNO ELECTRIC (MALAYSIA) SDN. BHD.

Catalogue No. CA000001455

1-A-2011